
PRODUCT DATA DRAWING



MATERIAL:

CONNECTORS: THREADED SMPM R/A FEMALE (3222-40060)

SMA MALE (SF2911-60172)

CABLE: FLEXIBLE Ø.047 CABLE (200-70-479)

SHRINK TUBING: M23053/5

PERFORMANCE:

IMPEDANCE: FREQ. RANGE: 50 OHMS DC TO 18.0 GHz.

MATERIAL:	SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/64 ANGULAR: X* ±1°0'			S		
FINISH: SEE NOTES		X°X' ±15' DECIMAL: .X ±.030 .XX ±.010	 ALL DIMENSIONS ARE AFTER PLATING. BREAK CORNERS & EDGES. 005 R. MAX. CHAM. 15T & LAST THREADS. SURFACE ROUGHNESS 63+MIL-STD-10. DIA: S ON COMMON CENTERS TO BE CONCENTRIC 		www.svmicrowave.com		
SURFACE AREA: N/A		.XXX ±.005			TITLE: THREADED SMPM R/A FEMALE TO SMA MALE 12" .047 CABLE		
	PROPRIETARY	PER ASME Y14.5M - 1994 THIRD ANGLE PROJECTION	DRAWN:	SJ 12/11/23		ASSEMBLY	
IS THE SOLE F ANY REPROD	PROPERTY OF EV MICROWAVE, INC. UCTION IN PART OR AS A WHOLE E WRITTEN PERMISSION OF		CHECKED:	SEE PDM	SIZE DWG. NO.	7032-9896	
	VE, INC IS PROHIBITED.		APPROVED:	SEE PDM	SCALE: 5:1	SHEET 1 OF 1	

REVISION HISTORY							
REV	DESCRIPTION	DATE	APPROVED				
-	NRN 47934	12/23					
			SEE PDM				