
PRODUCT DATA DRAWING



MATERIAL:

SIZE 12 STRAIGHT PIN CONNECTOR (9341-40063) MCX STRAIGHT CRIMP PLUG CONNECTORS:

CABLE: RG-179/U CABLE (200-70-118)

STRAIN RELIEF: M23053/5

PERFORMANCE:

IMPEDANCE: FREQ. RANGE: 75 OHMS DC TO 3.0 GHz.

NOTES:

- SIZE 12 PIN DESIGNED TO MATE TO SIZE 12 SOCKET CONTACT (9351-40045) ON 7093-0277, OR SIMILAR. SIZE 12 PIN WILL NOT MATE TO STANDARD SIZE 12 SOCKET CONTACT OR SMPM CONNECTOR. 1.
- 2.

MATERIAL:	SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: +1/64 ANGULAR: X° +1°0'	UNLESS
FINISH:	SEE NOTES	DECIMAL: X ±.030 .XX ±.010	1) ALL DIMENSION 2) ALL DIMENSION 3) BREAK CORNER 4) CHAM, 1ST & LA
SURFACE AREA: N/A		.XXX ±.005	5) SURFACE ROUG 6) DIA.'S ON COMM WITHIN .005 T.I. 7) REMOVE ALL BU
PROPRIETARY		PER ASME Y14.5M - 1994	.,
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SV MICROWAVE, INC. – ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SV MICROWAVE, INC IS PROHIBITED.		THIRD ANGLE PROJECTION	DRAWN:
			CHECKEE
			APPROVE

REVISION HISTORY				
REV	DESCRIPTION	DATE	APPROVED	
-	DCN 50993	08/21		
			SEE PDM	

OTHERWISE SPECIFIED NS ARE IN INCHES [MILLIMETERS] NS ARE AFTER PLATING. FRS & EDGES .005 R. MAX. AST THREADS.	Amphenol WWW.svmicrowave.com		
AGT I THREADS. IGHNESS 63-MIL-STD-10. IMON CENTERS TO BE CONCENTRIC J.R. BURRS	SIZE 12 STR. PIN TO MCX STR. PLUG RG179 CABLE		
TSW 08/26/21		ASSEMBLY	
D: SEE PDM	BIZE DWG. NO.	7093-0278	
ED: SEE PDM	SCALE: 4:1	SHEET 1 OF 1	